



# AIR COOLERS

	DARK ROCK ELITE	DARK ROCK PRO 5	DARK ROCK 5	DARK ROCK SLIM	DARK ROCK TF 2
Color options	-				
Model number	BK037	BK036	BK035	BK024	BK031
Dimensions, incl. fan (L x W x H in mm)	145 x 136 x 168		101 x 136 x 161	72 x 127 x 160	163 x 140 x 134
Weight incl. fan (kg)	1.33	1.29	1.03	0.62	0.95
Socket compatibility	Intel: 1700 / 1200 / 1150 / 1151 / 1155 AMD: AM5 / AM4			Intel: 1700 / 1200 / 2066 / 1150 / 1151 / 1155 / 2011(-3) Square ILM AMD: AM5 / AM4	
Maximum cooling capacity (W TDP)	280	270	210	180	230
Number of heat pipes / diameter (mm)	7 / 6	7 / 6	6 / 6	4 / 6	6 / 6
Audible noise (dB(A)) at 50 / 75 / 100% rpm	18.4 / 28.3 / 35.4 (Performance Mode) 11 / 19.5 / 25.8 (Quiet Mode)	15.1 / 25.9 / 32.3 (Performance Mode) 8.9 / 16.3 / 23.3 (Quiet Mode)	11.9 / 23.2 / 29.8	11 / 16.9 / 23.6	11.1 / 19.7 / 27.1
Fan type	Silent Wings 135mm PWM	Silent Wings 120mm PWM Silent Wings 135mm PWM	Silent Wings 4 120mm PWM	Silent Wings 3 120mm PWM	Silent Wings 3 135mm PWM Silent Wings 135mm PWM
Fan motor technology	6-pole fan motor				
Bearing type	Fluid Dynamic Bearing				
Fan dimensions (L x W x H in mm)	135 x 25 x 135	120 x 25 x 120 / 135 x 25 x 135	120 x 25 x 120		135 x 22 x 135 / 135 x 25 x 135
Fan speed (rpm) at 100% PWM	2000 (Performance Mode) 1500 (Quiet Mode)	2000 / 1700 (Performance Mode) 1500 / 1300 (Quiet Mode)	2100	1500	1400
Lifetime at 25°C (h)	300,000				
Thermal grease	Included				



## SHADOW ROCK 3    SHADOW ROCK SLIM 2    SHADOW ROCK TF 2    SHADOW ROCK LP

<ul style="list-style-type: none"><li>■ Impressive cooling performance of 190W TDP</li><li>■ Decoupled Shadow Wings 2 120mm PWM high-speed fan</li><li>■ Asymmetrical construction avoids blocking memory slots in front of the cooler</li><li>■ Five 6mm high-performance nickel-plated copper heat pipes</li></ul>	<ul style="list-style-type: none"><li>■ Very high cooling capacity of 160W TDP</li><li>■ Silence-optimized 135mm be quiet! PWM fan</li><li>■ 9 airflow-optimized fan blades and rifle-bearing</li><li>■ 4 high-performance 6mm heat pipes</li></ul>	<ul style="list-style-type: none"><li>■ Very high cooling capacity of 160W TDP</li><li>■ Silence-optimized 135mm be quiet! PWM fan</li><li>■ Small, diagonally arranged fins</li><li>■ 5 high-performance 6mm heat pipes</li></ul>	<ul style="list-style-type: none"><li>■ High cooling capacity of 130W TDP</li><li>■ be quiet! Pure Wings 2 120mm PWM fan</li><li>■ User-friendly mounting from atop the mainboard</li><li>■ Premium aluminum top cover</li></ul>
Silver   White	-		
BK004   BK005	BK032	BK003	BK002
121 x 130 x 163	74 x 137 x 161	137 x 165 x 112	134 x 122 x 76
0.71	0.69	0.68	0.39
Intel: 1700 / 1200 / 2066 / 1150 / 1151 / 1155 / 2011(-3) Square ILM AMD: AM5 / AM4		Intel: 1200 / 2066 / 775 / 1150 / 1151 / 1155 / 1156 / 1366 / 2011(-3) Square ILM AMD: AM4 / AM3 (+) / AM2(+) / FM1 / FM2(+)	Intel: 1700 / 1200 / 2066 / 1150 / 1151 / 1155 / 2011(-3) Square ILM AMD: AM5 / AM4
190	160		130
5 / 6	4 / 6	5 / 6	4 / 6
11.5 / 17.5 / 24.4	11.5 / 18.7 / 23.7	11.9 / 19.3 / 24.4	14.8 / 18.6 / 25.5
Shadow Wings 2 120mm PWM High-Speed	silence-optimized be quiet! fan		Pure Wings 2 120mm PWM
4-pole fan motor			
Rifle			
120 x 25 x 120	135 x 22 x 135		120 x 25 x 120
1600	1400		1500
80,000			
Included	Already applied		



## PURE ROCK PRO 3 LX    PURE ROCK PRO 3    PURE ROCK 3 LX    PURE ROCK 3

	<ul style="list-style-type: none"><li>▪ Impressively high cooling capacity of 250W TDP</li><li>▪ Light Wings LX 120mm PWM fans with funnel shaped air outlets</li><li>▪ 6 high-performance 6mm heat pipes</li><li>▪ Compatible with liquid metal thermal paste</li></ul>	<ul style="list-style-type: none"><li>▪ Impressively high cooling capacity of 250W TDP</li><li>▪ 2 optimized Pure Wings 3 120mm PWM fans with funnel shaped air outlet</li><li>▪ 6 high-performance 6mm heat pipes</li><li>▪ Compatible with liquid metal thermal paste</li></ul>	<ul style="list-style-type: none"><li>▪ Very high cooling capacity of 190W TDP</li><li>▪ Light Wings LX 120mm PWM fan with funnel shaped air outlet</li><li>▪ 4 black high-performance 6mm heat pipes</li><li>▪ Preinstalled cooler mounting bridge</li></ul>	<ul style="list-style-type: none"><li>▪ Very high cooling capacity of 190W TDP</li><li>▪ Pure Wings 3 120mm PWM fan</li><li>▪ 4 black high-performance 6mm heat pipes</li><li>▪ Preinstalled cooler mounting bridge</li></ul>
Color options	-	Silver   Black	-	
Model number	BK043	BK041   BK042	BK040	BK039
Dimensions, incl. fan (L x W x H in mm)	114 x 124 x 155		71 x 124 x 154	
Weight incl. fan (kg)	1.08		0.57	
Socket compatibility	Intel: 1851 / 1700 / 1200 / 1150 / 1151 / 1155 AMD: AM5 / AM4			
Maximum cooling capacity (W TDP)	250		190	
Number of heat pipes / diameter (mm)	6 / 6		4 / 6	
Audible noise (dB(A)) at 50 / 75 / 100% rpm	14.0 / 26.5 / 34.8		12.4 / 24.4 / 31.2	
Fan type	Light Wings LX 120mm PWM	Pure Wings 3 120mm PWM	Light Wings LX 120mm PWM	Pure Wings 3 120mm PWM
Fan motor technology	4-pole fan motor			
Bearing type	Rifle			
Fan dimensions (L x W x H in mm)	120 x 25 x 120			
Fan speed (rpm) at 100% PWM	2000			
Lifetime at 25°C (h)	60,000	80,000	60,000	80,000
Thermal grease	Already applied			



AIR COOLERS

PURE ROCK LP

PURE ROCK SLIM 2

- Solid cooling efficiency of 100W TDP
  - be quiet! 45mm high-quality fan
  - Extremely compact design for small form factor systems
  - 3 high-performance 6mm heat pipes
- High cooling efficiency of 130W TDP
  - be quiet! Pure Wings 2 92mm PWM fan
  - Optimized AMD mounting
  - Three 6mm heat pipes

Color options	-	
Model number	BK034	BK030
Dimensions, incl. fan (L x W x H in mm)	92 x 92 x 45	82 x 97 x 135
Weight incl. fan (kg)	0.35	0.39
Socket compatibility	Intel: 1700 / 1200 / 1150 / 1151 / 1155 AMD: AM5 / AM4	Intel: 1700 / 1200 / 2066 / 1150 / 1151 / 1155 AMD: AM5 / AM4
Maximum cooling capacity (W TDP)	100	130
Number of heat pipes / diameter (mm)	3 / 6	3 / 6
Audible noise (dB(A)) at 50 / 75 / 100% rpm	13.3 / 23.8 / 30.6	13.1 / 19.2 / 25.4
Fan type	be quiet! 45mm high-quality fan	Pure Wings 2 92mm PWM
Fan motor technology	4-pole fan motor	
Bearing type	Rifle	
Fan dimensions (L x W x H in mm)	92 x 25 x 92	92 x 25 x 92
Fan speed (rpm) at 100% PWM	2500	2000
Lifetime at 25°C (h)	80,000	
Thermal grease	Already applied	