

DARK POWER 13

NO COMPROMISE SILENCE AND PERFORMANCE

1000W • 850W • 750W

IDEAL APPLICATIONS

Advanced, high-resolution gaming with latest graphics cards
Overclocked next-gen systems
Media creation and render workstations

HIGHLIGHTS

Highest efficiency available (80 PLUS® Titanium)
Fulfills all ATX 3.1 specifications
Full compatibility with both PCIe 5.1 and PCIe 6+2 GPUs
Frameless Silent Wings fan for virtually inaudible operation

No Compromise Silence And Performance

The be quiet! Dark Power 13 offers 80 PLUS® Titanium efficiency, virtually inaudible operation, and ATX 3.1 compliance for next-gen GPU compatibility.

Highlights

- 80 PLUS Titanium efficiency (up to 95.8%)
- ATX 3.1 PSU with full support for PCIe 5.1 GPUs and GPUs with 6+2 pin connector
- Handles massive power excursions
- Improved and patented frameless Silent Wings fan for virtually inaudible operation
- Full mesh front with funnel shape air inlet upholds the high air circulation abilities
- Overclocking key switches between four 12V rails and one massive 12V rail
- Active Rectifier + full bridge LLC technology provides unmatched signal stability and extremely high efficiency at all loads
- One PCIe 5.1 12V-2x6 600W and 4 PCIe 6+2 connectors for overclocked high-end GPUs
- Modular cable management for maximum convenience
- 10-year manufacturer's warranty

DARK POWER 13

NO COMPROMISE SILENCE AND PERFORMANCE

Technische Daten				
IN GENERAL	Model	1000W	850W	750W
	Article no.	BN335	BN334	BN333
	EAN Code	4260052189405	4260052189399	4260052189382
	Voltage (Vac) / Frequency (Hz)	100 - 240 / 50 - 60		
	Dimensions (L x W x H) (mm)	175 x 150 x 86		
	ATX 12V 3.1 / ATX 12V 2.x / EPS 12V 2.92	✓ / ✓ / ✓	- / ✓ / ✓	- / ✓ / ✓
	Wire-free (DC-side)	✓		
	Silent Wings fan (mm)	135		
	Noise level (dB(A)) at 10 / 20 / 50 / 100% load	8.1 / 8.1 / 8.6 / 25.8	7.5 / 7.5 / 7.6 / 19.8	7.9 / 8.5 / 9 / 18.8
	12V rail (Multi-Rail) / 12V Single Rail	4 / ✓		
	Overclocking Key / Jumper	✓ / ✓		
	Power Good signal (ms)	100-150		
	PFC	active		
	Certification	80 PLUS® Titanium		
	Efficiency (%) at 230V, 2% / 10% / 20 % / 50% / 100% load	72 / 90.7 / 94.8 / 95.2 / 93.3	73.6 / 92 / 94.7 / 95.4 / 93.5	72.2 / 91.8 / 94.8 / 95.8 / 93.8
	Energy Star 8.0 compatible	✓		
	ErP ready / Power in stand-by (W)	✓ / <0.13		
OCP, OVP, UVP, SCP, OPP, OTP	✓			
Lifetime of PSU at 25°C (h)	>100,000			
CABLES	No. of cables	12		
	Maximum cable length (cm)	105		
	Length of ATX-connection cable (cm)	60		
	Cable management	Modular		
	Sleeved cables	✓		
CONNECTORS	ATX motherboard (20+4 pin)	✓		
	12V-2x6 cable W	1 600		
	PCI express (6+2 pin)	4		
	P8-/P4-connector	1x P4+4 / 1x P8		
	S-ATA	13	12	
	P-ATA	2		

Output Data

AC Input		100 - 240Vac 50 - 60Hz 13 - 6A							
DC Output		3.3V	5V	12V1	12V2	12V3	12V4	-12V	5VsB
1000W	Max. Current	25A	25A	32A	32A	40A	40A	0.5A	3A
	Max. Combined Power	125W		996W				6W	15W
		1000W							

AC Input		100 - 240Vac 50 - 60Hz 10 - 5A							
DC Output		3.3V	5V	12V1	12V2	12V3	12V4	-12V	5VsB
850W	Max. Current	24A	24A	30A	30A	35A	35A	0.5A	3A
	Max. Combined Power	120W		840W				6W	15W
		850W							


AC Input		100 - 240Vac 50 - 60Hz 9 - 4.5A							
DC Output		3.3V	5V	12V1	12V2	12V3	12V4	-12V	5VsB
750W	Max. Current	22A	22A	25A	25A	30A	30A	0.5A	3A
	Max. Combined Power	110W		744W				6W	15W
		750W							

NO COMPROMISE SILENCE AND PERFORMANCE

1000W



Dimensions



e-mail: service@bequiet.com
Visit the contact section on
bequiet.com for the right regional
service information.